

PRODUCT BRIEF
Intel® Integrated RAID
Module RMS2MH080

Intel® Integrated RAID Module RMS2MH080

Simplifies Adding Full Featured SAS-2 RAID to Select Intel® Server Boards and Systems

Product Overview:

The Intel® Integrated RAID Module RMS2MH080, powered by LSI MegaRAID® technology, offers intelligent RAID protection for servers using SAS or SATA hard drives. Designed specifically for select Intel server boards, this SAS/SATA module allows for use in popular 1U and 2U servers without sacrificing a valuable riser-card slot or using a chassis with low-profile add-in card cut-outs.

Engineered for mainstream use, the RMS2MH080 is a powerful internal SAS/SATA RAID solution with integrated LSI2108 RAID-On-Chip, a PCI Express x8 Gen 2.0 host interface and 800MHz DDR2 memory. It can connect up to eight SAS or SATA hard drives directly, or up to thirty two using SAS expanders. This module also supports an optional Intel RAID Smart Battery, AXXR5BBU7, which protects cached data by providing power to the module in the event of server or power failure.

All Intel RAID solutions are validated across multiple platforms with Intel® boards, chassis, and systems. Custom training, as well as Intel® service and support, make Intel the one source for customers seeking data protection, increased productivity, and simplified IT.


KEY Advantages:

- **Greater flexibility of system design.** Eliminate the need to use a riser card or a standard add-in card slot. 1U capable system board connects to the I/O expansion slot on Intel's rack optimized server boards and is compatible with Intel or 3rd party chassis.
- **Exceptional data protection.** Supports data redundancy using SAS or SATA hard disk drives through mirroring, parity, and double parity (RAID levels 1, 5, and 6) plus striping capability for spans (RAID levels 10, 50, and 60).
- **Excellent performance.** Enhances I/O of mainstream applications with LSI SAS2108 ROC technology, PCI Express*2.0 Gen x8 host interface and 800 MHz cache.
- **Outstanding availability.** Delivers proactive drive monitoring and automatic error correction. Maintain data in the event of power or server failure with optional battery backup.
- **Increased IT productivity.** Offers easy installation, simplified administration, and advanced management capabilities; as, it features a suite of tools that are common across all Intel SAS/SATA RAID solutions.



Features:

- 1 Embedded 512 MB 800 MHz cache (ECC DDR2 memory) to efficiently store data in transition
- 2 Speaker to deliver audible alerts
- 3 Two SFF8087 SAS/SATA connectors for up to eight internal ports
- 4 x8 PCI Express Generation 2 interface for fast communication with the server board
- 5 LSI SAS2108 ROC controller providing SAS 2.0 compliance including 6Gb/s data transfer
- 6 Optional Intel® Smart Battery AXXRSBBU7 for up to 72 hours of cache data retention
- 7 Optional Premium Feature Key for upgrade features such as SSD Cache, FastPath* I/O or Rapid Recovery Snapshot
- 8 Includes two internal cables with SFF8087 connectors that expand to four individual connectors, cables ship with standard SKU (not shown)



Technical Specifications:

Intel Order Code	AXXRMS2MH080
Compatible Intel® Server Boards and Systems	Intel® Server Board S5520UR Intel® Server Board S5500WB Intel® Server System's based on the above server boards such as SR1625UR, SR2600UR and SR2612UR.
RAID Levels and Spans	RAID Levels 0, 1, 5, and 6 RAID Spans 10, 50, and 60
Fault Tolerant Features	Online Capacity Expansion Hot-Spare Support Enclosure Management S.M.A.R.T Support
Intel® RAID Software	Intel® RAID Web Console 2 Intel® RAID Flash Utilities
I/O Processor	LSI SAS2108 ROC running at 800MHz
Drive Types	SAS or SATA 6Gb/s or 3Gb/s
Maximum Drives	Up to 32 physical devices supported
Connectors	Two SAS SFF8087 x4 SAS internal connectors
Cache Memory	Embedded 512MB DDR2 (800MHz)
PCI Interface	PCI Express* 2.0 x8
BBU Support	Intel® Smart Battery AXXRSBBU7
Form Factor	Custom for use with select Intel Server boards
Data Transfer Rates	Up to 6Gb/s per port
Operating Temperature	Maximum ambient: 50°C (45°C with optional BBU)
Operating Voltage	+3.3 V

For more information on how to make Intel® Integrated RAID Module RMS2MH080 part of a successful storage solution, visit: www.intel.com/go/RAID



INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

Intel and the Intel logo are trademarks of Intel Corporation in the U.S. and other countries.

*Other names and brands may be claimed as the property of others.

Copyright © 2010 Intel Corporation. All rights reserved.

Printed in USA

0610/SJ/ExactMarket/PDF

Please Recycle

324034-001US

